

## CAMMS™View Building Security Surveillance Module



CAMMS™View provides instant situational awareness for first responders, security firms and others requiring immediate visual information in both critical and non-critical situations.

The CAMMS™View module is a 19" rack mount component that quickly and easily connects to existing surveillance infrastructure and securely transmits video to a CAMMS™ mobile mesh network. No configuration is required and existing cameras and controllers do not need to be changed to enable CAMMS™View. Surveillance video can be streamed 24/7 or upon an alarm activation signal.

CAMMS™View is capable of storing digital files such as building plans, evacuation routes, etc. enabling CAMMS™ mobile users to download these files for sharing over a CAMMS™ mobile mesh network.



CAMMS™View offers a quick and cost effective solution for establishing new or temporary video surveillance systems and is also ideal for supplementing or expanding existing video surveillance systems installed in such locations as banks, hospitals, campuses, or any public area.



*Arrive on scene, connect wirelessly to building/location's existing surveillance system and view digital files of building floor plans and video from existing surveillance system.*



Rack mount, lockable aluminum enclosure  
24hr battery back up  
1, 2, 4, 8+ analog video connection  
Dual radio transmission, 2.4 GHz and 4.9 GHz (Public Safety)

Video (Compression)  
Compression MPEG-4 compliant compression  
Resolution Full D1 (720x480 NTSC, 720x576 PAL)  
CIF (352x240 NTSC, 352x288 PAL)  
QCIF (160x112 NTSC, 176x144 PAL)

Image Frame Rate 30 fps at full D1 res (NTSC)  
25 fps at full D1 res (PAL)

Video Input  
Composite Input CVBS, 1.0Vp-p with 75Ω loading,  
BNC connector

Video Output  
Composite Output CVBS, 1.0Vp-p with 75Ω loading,  
BNC connector

Audio Input  
Compression 8 kHz, Mono, PCM  
Audio Line Input Unbalanced, 1.0 Vpp, 1 Vrms, 3.5mm jack

Audio Output  
Compression 8 kHz, Mono, PCD  
Audio Line Output Unbalanced, 1.0 Vpp, 1 Vrms, 3.5mm jack

Alarm  
Input 2, TTL, terminal block  
Output 2, TTL, terminal block

10/100 BASE T Switch  
Micro computer P4  
External and internal antennas



Command Anywhere  
**CAMMS™  
VIEW**

**for further information please contact:**

The Americas:  
Global Mesh Technologies Service  
Ph: 407 965 0620

Worldwide:  
Command Anywhere Pty. Ltd.  
Ph: +61 8 7123 3054  
commandanywhere.com